Datasheet

HP EliteDisplay E242 24-inch Monitor Head Only



Be a master at multi-tasking with HP EliteDisplay E242 24-inch Monitor Head Only, which delivers Full HD resolution and an extra-large screen for all of your work.



Room to navigate.

• See more of your work onscreen at the same time with 1920 x 1200 resolution¹ and a 16:10 aspect ratio on a 24-inch diagonal screen. Collaborate easily with 178-degree viewing angle IPS technology that gives almost everyone in the room a great view.

Ports for your platforms and peripherals.

• Connect to a range of PCs and USB devices with HDMI, DisplayPort, VGA, and USB ports.

Reduce power consumption and help lower costs.

- Get an intelligent, energy-efficient design that is ENERGY STAR[®] certified, EPEAT[®] Gold registered², and meets TCO Certified Edge requirements. It also has mercury-free display backlights, low halogen³, and arsenic-free display glass.
- Design the screen for how you work with HP Display Assistant software.
- Customize a complete solution with HP accessories.⁴ Add audio with the HP Speaker Bar, an HP Single Arm for easy mounting, or a HP USB Graphics Adapter for multi-monitor4 setups.
- Get three years of service and support, and extend your protection with optional HP Care Packs.⁵

HP EliteDisplay E242 24-inch Monitor Head Only Specifications Table



Display Type PS w/LED baddight Panel Active Area 518.4 x32.0 mm Display Size (diagonal) 60.96 cm (24') Viewing Angle 77 horizontal; 178" writical Brightness 250 cdm ²⁺¹ Contrast Ratio 1000-1 static; 500000-1 dynamic ' Response Time 7 m g ray to gray ' Product colour Black Aspect Ratio 16-10 Native Resolution 1920x 1200; 660 Hz Resolutions Supported 1820x 1200; 650 x1050; 1600 x1200; 1600 x1020; 1600 x1020; 1200 x1024; 1280 x00; 1280 x720; 1024 x768; 800 x600; 720 x400 Display Features Anti-glarc; In plane switching; Language selection; LED Baddights; On-scoren controls; Pivot rotation; Plang r4:9; OF Power Input Signal 1 Vie.1 HDBH (with HDCP support) 1 DisplayPert 1.2 (with HDCP support) Porter consumption 3 USR 2.0 Time downstream and one upstream) * Input Signal 1 Vie.1 HDBH (with HDCP support) 1 DisplayPert 1.2 (with HDCP support) Power Consumption 3 USR 2.0 Time downstream and one upstream) * Input Signal 1 Vie.1 HDBH (with HDCP support) 1.2 (with HDCP support) Prote consumption 3 USR 2.0 Time downstream and one upstream) * Upstream Consumption 3 USR 2.0 Time downstream and one upstream) * Upstream Consumption 3 USR 2.0 Life Addition Separately) Resider Sing Mareider, 2:0 Dis Sing Ma<				
Display Size (diagonal) 60.96 cm (24") Viewing Angle 178" horizontal; 178" vertical Brightness 250 cd/m² i Contrast Ratio 1000 i static: 5000000:1 dynamic ' Response Time 7 ms gray to gray ' Product colour Black Aspect Ratio 16:10 Native Resolution 1920 x 1200 (160 ± 100 x 1000; 1600 x 1000; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 × 600; 720 x 400 Bisplay Features Anti-glare; In plane switching; Language selection; LED Backlights; On -screen controls; Plvot rotation; Plug and Plag; User programmable; User controls User Controls Monu; Mirus C*1; Plus C*1*; 0; Plower Input Signal 1 VK-1 HBM (with HECP support): 1.0 splayPert 1.2 (with HECP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) * Input Signal 1 VK-2 HBM (with HECP support): 1.0 splayPert 1.2 (with HECP support) Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x X x H) 2.2 kg Head only Physical security Gouring temperature : 5 to 35% (Compliance Energy Efficioncy Compliance Certified Compliance </td <td>Display Type</td> <td>IPS w/LED backlight</td>	Display Type	IPS w/LED backlight		
Viewing Angle 178* horizontal; 178* vertical Brightness 250 cd/m*1 Contrast Ratio 1000-1 static; 5000000:1 dynamic 1 Response Time 7 ms gray to gray 1 Product colour Black Aspect Ratio 16:10 Native Resolution 1920 x 1200 (#0.0 Hz Resolutions Supported 1920 x 1200 (#0.0 Hz Bisplay Features Anti-glare; In plane switching; Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls User Controls Manu, Minus (**, Plug, (**), DK; Power Input Signal 1 VGA; 1 HdMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Power Consumption 38 W (maximum); 30 W (yaical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x D x H) Sccurity Inde-ready Block is sold separately) Features Certification and (W x D x H) Physical security Sccurity Inde-ready Block is sold separately) Features Certification and (Paseting humidity: 20 to 80% RH	Panel Active Area	518.4 x 324.0 mm		
Brightness 250 cd/m² 1 Contrast Ratio 1000.1 stalic; 5000000.1 dynamic 1 Response Time 7 m5 gray to gray 1 Product colour Black Aspect Ratio 16:10 Native Resolution 1920 x 1200 @ 60 Hz Resolutions Supported 1920 x 1200, 1920 x 1080, 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400 640 x 400 Josplay Features Anti-glare; In plane switching; Language selection; LED Backlights; On-screen controls; Plwot rotation; Plug and Play; User programmable; User controls User Controls Menu; Ming: (**); Plus (**); OK; Power Input Signal 1 VGA; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Power Input votage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without; 56.22 x 5 x 3.774 cm Stand (W x D x H) Security lock-ready (lock is sold separately) features Security Inck-ready (lock is sold separately) features Coperating humidity; 200 to 306 RH Environmental Operating humidity; 500 9241-307; EAC; UL; CC; CC; CE; CEE; SERP; TCO Centified Edge; SC; VCCI; FCC; BSM; WEEE; SmartWey Transport Partnership - NA only Environmental CP:CE; KCACC; NMM; PSE;	Display Size (diagonal)	60.96 cm (24")		
Contrast Ratio 1000:1 static; 5000000:1 dynamic ' Response Time 7 ms gray to gray ' Product colour Black Aspect Ratio 16:10 Native Resolution 1920 x 1200 @ 60 Hz Resolutions Supported 1920 x 1200 (1920 x 1080; 1600 x 1050; 1600 x 1200; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400 Display Features Anti-glare; In plane switching: Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls User Controls Menu; Minus (-*); DK; Power Input Signal 1 VGA; 1 HDM (with HDCP support); 1 DisplayPert 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (two downstream and one upstream) ' Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum); 30 W (typical); 0.5 W (standby) Dimensions without 5.6.22 x 5 x 37.74 cm Stand (W x X H) 4.2 kg Head only Head only Physical security Security lock-ready lock is sold separately) features Operating temperature: 5 to 357C Comparating temperature: 5 to 357C Operating temperature: 5 to 357C Compliance CE: (CE; KC/KCC; NOM; PSB; (E; TUV-S; ISO 9241-30	Viewing Angle	178° horizontal; 178° vertical		
Response Time 7 ms gray to gray i Product colour Black Aspect Ratio 16:10 Native Resolution 1920 x 1200 @ 60 Hz Resolutions Supported 1920 x 1200 m 1600 x 1000; 1600 x 1000; 1600 x 1200; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400 Display Features Anti-glane; in plane switching; Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls User Controls Menu; Minus (-*); Plus (*+); OK; Power Input Signal 1 VGA; 1 HDM (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) * Input Signal 1 VGA; 1 HDM (with HDCP support); 10 kplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) * Input Signal 1 VGA; 1 HDM (with HDCP support) Power Consumption 38 W (maximum); 30 W (ypical), 0.5 W (standby) Dimensions without 56-22 x 5 x 3.74 cm Stand (W x D x H) 4.2 kg Head only Physical security Security lock-ready flock is sold separately) features Compliance CE: (KC/KCC; NOM; PSB; (EE; TUV-S; ISO 9241-307;	Brightness	250 cd/m ² 1		
Product colour Black Aspect Ratio 16:10 Native Resolution 1920 x1200 @ 60 Hz Resolutions Supported 1920 x1200; 1920 x 1080; 1680 x1050; 1600 x1200; 1600 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400 Display Features Anti-glare; In plane switching: Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls User Controls Menu; Minus (**); Plus (**); OK; Power Input Signal 1 VGA; 1 HDMI (with HDCP support): 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) * Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x D x H) 42 kg Head only Head only Physical security Security lock-ready (lock is sold separately.) features Environmental Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency ENERGY STR* certified Compliance Transport Partnership - No only Certiffication and certifications Ce	Contrast Ratio	1000:1 static; 5000000:1 dynamic ¹		
Aspect Ratio 16:10 Aspect Ratio 16:10 Native Resolution 1920 x 1200 @ 60 Hz Resolutions Supported 1920 x 1200; 1920 x 1080; 1680 x 1050; 1600 x 1200; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400 640 x 480 Display Features Anti-glare; In plane switching: Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls Men; Minus ("-); Plus ("-); OK; Power Input Signal 1 VGA; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) 1 Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without Stand (W x D x H) Weight 4.2 kg Head only Physical security features Environmental Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Compliance Certification and CE; CB; KC/KCC; NOM; PSB; ICE; TUV-5; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCC; FCC; BSM; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2 Specifications What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP; Including a 3-year standard limited warranty. Optional Care Pack. Services are extended service contracts which go beyond your standard	Response Time	7 ms gray to gray 1		
Native Resolution 1920 x 1200 @ 60 Hz Resolutions Supported 1920 x 1200; 1920 x 1080; 1680 x 1050; 1600 x 1200; 1600 x 900; 1240 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400 G4U x 480 Display Features Anti-glare; in plane switching; Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls User Controls Menu; Minus (*-?); Plus (*-?); OK; Power Input Signal 1 VGA; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) ¹ Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x D x H) Veck Weight 4.2 kg Head only Physical security Features Operating temperature: 5 to 35°C Environmental Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Compliance CE; CE; KC/KCC; NOM; PSB; ICE; TUV-5; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCC; FCC; BSM; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercu	Product colour	Black		
Resolutions 1920 x 1200; 1920 x 1080; 1680 x 1050; 1600 x 1200; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400 G40 x 480 Display Features Anti-glare; In plane switching; Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls User Controls Menu; Minus (*-?); Plus (*-?); OK; Power Input Signal 1 VGA; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) 1 Input Voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Sec.22 x 5 x 37.74 cm Stand (W x 0 x H) 4.2 kg Head only Physical security Security lock-ready (lock is sold separately) features Environmental Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Compliance Certification and CE: CE: KC/KCC; NDM: PSB; ICE: TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display backlighting; Low halogen 2 Specifications What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) What's in the box	Aspect Ratio	16:10		
640 x 480 Display Features Anti-glare; In plane switching; Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls User Controls Menu; Minus (*-?); Plus (*+?); OK; Power Input Signal 1 VGA; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) 1 Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x D x H) Security Icock-ready (lock is sold separately) features Deparating temperature: 5 to 35*C Operating temperature: 5 to 35*C Operating temperature: 5 to 35*C Operating humidity: 20 to 80% RH Encryp Efficiency Certification and ce:, GB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCC; PCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Specifications Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2 Specifications Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guid	Native Resolution	1920 x 1200 @ 60 Hz		
User Controls Menu; Minus (*-*); Plus (*+*); OK; Power Input Signal 1 VGA; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) * Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x D x H) 56.22 x 5 x 37.74 cm Weight 4.2 kg Head only Physical security Security lock-ready (lock is sold separately) features Coperating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Specifications Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2* What's in the box Monitor, AC power cord; VGA cable; US cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, Including a 3-year standard limited warranty. Optional Care Pack Services are extended service contrac	Resolutions Supported			
Input Signal 1 VGs; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support) Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) 1 Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x D x H) 56.22 x 5 x 37.74 cm Weight 4.2 kg Head only Physical security features Security lock-ready (lock is sold separately) Environmental Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 25°C Compliance Certification and compliance CE: CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2 Specifications Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HB; Including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard <td>Display Features</td> <td colspan="3">Anti-glare; In plane switching; Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls</td>	Display Features	Anti-glare; In plane switching; Language selection; LED Backlights; On-screen controls; Pivot rotation; Plug and Play; User programmable; User controls		
Ports and Connectors 3 USB 2.0 (Two downstream and one upstream) * Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without 56.22 x 5 x 37.74 cm Stand (W x D x H) 56.22 x 5 x 37.74 cm Weight 4.2 kg Head only Physical security features Security lock-ready (lock is sold separately) Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE: (E); KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2 Specifications Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, services are extended service contracts which go beyond your standard	User Controls	Menu; Minus ("-"); Plus ("+"); OK; Power		
Input Power Input voltage: 100 to 240 VAC Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without Stand (W x D x H) 56.22 x 5 x 37.74 cm Weight 4.2 kg Head only Physical security features Security lock-ready (lock is sold separately) Environmental Operating temperature: 5 to 35°C Operating temperature: 5 to 35°C Operating temperature: 5 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP, SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2 Specifications Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	Input Signal	1 VGA; 1 HDMI (with HDCP support); 1 DisplayPort 1.2 (with HDCP support)		
Power Consumption 38 W (maximum), 30 W (typical), 0.5 W (standby) Dimensions without Stand (W x D x H) 56.22 x 5 x 37.74 cm Weight 4.2 kg Head only Physical security features Security lock-ready (lock is sold separately) Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercury-free display backlighting; Low halogen ² Specifications Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	Ports and Connectors	3 USB 2.0 (Two downstream and one upstream) ¹		
Dimensions without Stand (W x D x H) 56.22 x 5 x 37.74 cm Weight 4.2 kg Head only Physical security features Security lock-ready (lock is sold separately) Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-5; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2 Specifications Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	Input Power	Input voltage: 100 to 240 VAC		
Stand (W x D x H) Weight 4.2 kg Head only Physical security features Security lock-ready (lock is sold separately) Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Arsenic-free display glass; Mercury-free display backlighting; Low halogen ² Specifications What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	Power Consumption	38 W (maximum), 30 W (typical), 0.5 W (standby)		
Head only Physical security features Security lock-ready (lock is sold separately) Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Specifications Arsenic-free display glass; Mercury-free display backlighting; Low halogen 2 What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP; including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard		56.22 x 5 x 37.74 cm		
features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Specifications Arsenic-free display glass; Mercury-free display backlighting; Low halogen ² What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	Weight			
Operating humidity: 20 to 80% RH Energy Efficiency Compliance ENERGY STAR® certified Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Specifications Arsenic-free display glass; Mercury-free display backlighting; Low halogen ² What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	•	Security lock-ready (lock is sold separately)		
Compliance Certification and compliance CE; CB; KC/KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; TCO Certified Edge; ISC; VCCI; FCC; BSMI; WEEE; SmartWay Transport Partnership - NA only Environmental Specifications Arsenic-free display glass; Mercury-free display backlighting; Low halogen ² What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	Environmental			
compliance Transport Partnership - NA only Environmental Specifications Arsenic-free display glass; Mercury-free display backlighting; Low halogen ² What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard	•• •	ENERGY STAR [®] certified		
Specifications What's in the box Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers) Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard				
Warranty Protected by HP, including a 3-year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard		Arsenic-free display glass; Mercury-free display backlighting; Low halogen ²		
	What's in the box	Monitor; AC power cord; VGA cable; USB cable; DisplayPort cable; CD (includes User Guide, warranty, drivers)		
	Warranty			

See important legal disclaimers on the last page

Recommended Accessories and Services

HP Adjustable Dual Display Stand		The HP Adjustable Dual Display Stand allows you to use two displays to maximize your productivity and optimize efficiency. Either or both displays can be rotated to landscape or portrait orientation, and the stand is depth-, height-, tilt-, and angle-adjustable so you can view both screens at eye-level as well as slightly facing each other, letting you track multiple applications and information sources at the same time. Integrated base rollers let you rotate the stand so you can more easily share your work. Product number: AW664AA
HP Single Monitor Arm		The HP Single Monitor Arm is the perfect desk accessory for your work life. Sleek and streamlined, the HP Single Monitor Arm is designed to complement the way you work. Product number: BT861AA
HP Quick Release Bracket		A secure and easy-to-use mounting solution for your VESA-compliant HP thin clients, compatible HP flat panel monitors and other HP desktop products. Attach to any a compatible stand, bracket or wall mount and make the most of your workspace. Product number: EM870AA
HP 5-year Next Business Day Onsite Large Monitor Hardware Support		Receive 5 years of next business day onsite repair from an HP-qualified technician for your computing device, if the issue cannot be solved remotely. For more information on Care Pack services, please visit www.hp.com/go/cpc. Product number: U7937E

Messaging Footnotes

¹ All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

² EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country.

³ External power supplies, power cords, cables, and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

⁴ Each sold separately.

⁵ Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP Services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Technical Specifications Footnotes

¹ All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower. ² External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

Sign up for updates hp.com/go/getupdated

The product could differ from the images shown. © 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. Specific features may vary from model to model. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR® and the ENERGY STAR® mark are registered trademarks of the U.S. Environmental Protection Agency.

