Fujitsu recommends Windows.

FUJITSU

Data Sheet FUJITSU LIFEBOOK A555 and LIFEBOOK A555G Notebook

Your Essential Powerful Partner

The FUJITSU Notebook LIFEBOOK A555 is a solid and reliable partner with a 39.6 cm (15.6-inch) anti-glare display offering comfortable viewing, even outdoors. Enjoy multimedia applications on the LIFEBOOK A555G's FHD display which features the AMD Radeon™ R7 M260 graphic card. The integrated WLAN and Bluetooth, HDMI, Anytime USB Charger and num pad keyboard provide you with convenient mobility.

Higher performance computing

Faster and more responsive

■ 5th generation Intel[®] Core[™] i5 processor

Connectivity and convenience on demand

Enjoy a variety of interfaces and technology to support you in fulfilling your demands at home and in the office

Integrated WLAN and Bluetooth, HDMI and VGA ports, LAN connector and Anytime USB Charger

Comfortable user experience

- Ergonomic comfort while working on daily challenges
- 39.6 cm (15.6-inch) anti-glare display, full-size keyboard with num pad

Excellent multimedia experience

Enjoy the power of discrete graphics and high definition viewing

■ AMD Radeon[™] R7 M260 with up to 2GB dedicated video memory and FHD display











Components

Operating systems			
Operating system	Windows 8.1 Pro 64-bit	Windows 8.1 Pro 64-bit	
	Windows 8.1 64-bit	Windows 8.1 64-bit	
	Windows 7 Professional 64-bit	Windows 7 Professional 64-bit	
Memory modules	4 GB (1 module(s) 4 GB) DDR3, 1,600 MHz, PC3-12800, SO DIMM		
	8 GB (1 module(s) 8 GB) DDR3, 1,600 MHz, PC3-12800, SO DIMM		
Hard disk drives (internal)	SSHD, 5,400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.		
	SSD SATA III, 256 GB, 2.5-inch		
	SSD SATA III, 128 GB, 2.5-inch		
	SATA, 5,400 rpm, 750 GB, 2.5-inch, S.M.A.R.T.		
	SATA, 5,400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.		
	SATA, 5,400 rpm, 1 TB, 2.5-inch, S.M.A.R.T.		
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.		
	Accessible capacity may vary, also depending on used software.		
	Internal HDD interface: S-ATA III (6GBit/s)		
Optical drive options	DVD Super Multi		
	Weight saver		
Interface add on cards/component	2		
(optional)			
WLAN (optional)	Intel® Wireless-N 7265 2x2 b/g/n with integrated Bluetooth 4.0		
	Intel® Dual Band Wireless-N 7265 2x2 ac with integrated Bluetooth 4.0		
Multimedia			
Camera	Built-in webcam (HD) with Status LED	Built-in webcam, Full HD	
Camera notes	1200x768 (0.9 megapixel)	1920x1080, 2.0 megapixel	

Base unit

Base unit	LIFEBOOK A555 LIFEBOOK A555/G	
General system information		
Processor	Intel® Core™ i5-5200U processor	Intel [®] Core™ i5-5200U processor
	(2 Cores / 4 Threads, 2.2 GHz, up to 2.7 GHz, 3 MB, Intel® HD Graphics 5500)	(2 Cores / 4 Threads, 2.2 GHz, up to 2.7 GHz, 3 MB, Intel® HD Graphics 5500)
Chipset	Integrated	Integrated
Memory slots	2 SO DIMM (DDR3, 1600 MHz)	2 SO DIMM (DDR3, 1600 MHz)
Supported capacity RAM (min.)	4 GB	4 GB
Supported capacity RAM (max.)	16 GB	16 GB
Memory notes	Dual channel support. DDR3L – 1,600 MHz	Dual channel support. DDR3L – 1,600 MHz
LAN	10/100/1,000 MBit/s Realtek RTL8111GS-CG	10/100/1,000 MBit/s Realtek RTL8111GS-CG
Audio type	On board	On board
Audio codec	Realtek ALC283 (HD audio)	Realtek ALC283 (HD audio)
Audio features	High Definition Audio, 2x built-in speakers (stereo), Sound High Definition audio, 2x built-in speakers (stereo), Sou volume control via function key (down: Fn+F8; up: Fn+F9) volume control via function key (down: Fn+F8; up: Fn+F	

ColorBlackBlackBlackMaterialMattMattMaterialMattMattDisplay39.6 cm (15.6-inch), LED backlipht, (HD), Ant-Jeglar display, 13.65.6.76.8 pixel. 300.1 (min), 201 of display, 13.65.6.76.8 pixel. 300.1 (min), 201 of display, 13.65.76.8 pixel. 300.1 (min), 201 of display, 13.67.7 (MD), 201 of display, 14.67.7	Product design			
Display 39.6 cm (15.6-inch), LED backlight, (HD), Anti-glan Display 39.6 cm (15.6-inch), LED backlight, (HD), Anti-glan Aspect rata 16.9 Brightness - typical 200 cd Contrast - typical 200 cd Schrast - typical 200 cd Contrast - typical 200 cd Capabits 1.920 x1 200 pixel Base unit LFEB00K A555 LFEB00K A555 LFEB00K A555 G Max. resolution external display 1.920 x1 200 pixel Graphits 1.920 x1 200 pixel Graphits for them DirectV* 11 3uppart DirectV* 11 3uppart DirectV* 11 3uppart DirectV* 11 DirectV* 11 3uppart DirectV* 11 3uppart DirectV* 11 3uppart DirectV* 11 DirectV* 11 3uppart DirectV* 11 3uppart DirectV* 11 3uppart DirectV* 11 DirectV* 11 3uppart DirectV* 12 DirectV* 11 3uppart		Black	Black	
Display99.6 or 115.6-inchi, LED Seckliphe, (HD), Ani-quare display, 1.320 x 1.080 pixel, 300.1 (min), 200 of display, 1.320 x 1.000 pixel90.6 (min), 200 of display, 1.320 x 1.000 pixelGraphics formation external display display, 1.200 pixel1.920 x 1.200 pixel1.920 x 1.200 pixelGraphics hard formation external display display, 1.200 pixel1.920 x 1.200 pixel1.920 x 1.200 pixelGraphics hard formation external display in pixot 1.200 pixel1.920 x 1.200 pixel1.920 x 1.200 pixelGraphics hard formation external display in pixot 1.200 pixel1.920 x 1.200 pixel1.920 x 1.200 pixelGraphics hard formation external display in pixot 1.200 pixel	Material	Matt	Matt	
Bisplay93 6.00 (15.6-inch), LED Backlight, (HD), Ann-Jare display, 1.30 x 1.080 packl, 300.1 (min), 200 cd display, 1.30 x 1.200 packl Display, 1.30 x 1.300 packl Display, 1.	Display			
Brightness - typical200 cd220 cdContrast - typical300 cl (min)300 cl (min)Compiles			39.6 cm (15.6-inch), LED backlight, (Full HD), Anti-glare display, 1,920 x 1,080 pixel, 300:1 (min), 220 cd	
Contrast - typical300:1 (min)300:1 (min)GraphicsBase unitLIFFBOOK ASS55IIFFBOOK ASS55GMax. resolution external display1,920 x 1,200 pixel1,920 x 1,200 pixelGraphics band nameIntel® HD Graphics S500Intel® HD Graphics S500, AMD Radeon® R7 MD50Graphics hand nameIntel® HD Graphics S500Intel® HD Graphics S500, AMD Radeon® R7 MD50Graphics notesShared memory depending on main memory sizeDedicated video memory2 GB (DDR3 VRAM)Shared video memoryup to 1.695 MBInterfacesDC-in1USB 2.0 total3 (1 x Anytime USB Charge Functionality_ depending on BIOS setting)VGAVGA1HDMI1Ethernet (R)+55)50/SD/ICSOXCKeyboard and pointing devicesSpil resistant isolated keyboard with number block Touchpad Satus LEDWireless technologiesSpil resistant isolated keyboard with number block Satus LEDWireless technologiesSpil resistant isolated keyboard with number blockWireless technologiesSpil resistant isolated keyboard with number blockButectonthv4.0Wireless technologiesSpil resistant isolated keyboard with number blockBu	Aspect ratio	16:9		
Graphics Graphi	Brightness - typical	200 cd	220 cd	
Base unit UFE800 K A555 UFE800 K A555 A320 0 picel 1.920 x 1.200 picel 1.920 x 1.920	Contrast - typical	300:1 (min)	300:1 (min)	
Base unit UFE800K AS55 UFE800K AS55 Max. resolution external display 1,920 x 1,200 pixel intel*H ID Gaphics 5500 AMD Radeon™ R7 M260 Graphics features DirectX* 11 support DirectX* 11.1 Graphics notes Shared memory depending on main memory size - 2 GB (DDR3 VPAM) External display memory depending on main memory size - 2 GB (DDR3 VPAM) 2 GB (DDR3 V	Graphics			
Graphics brand name Intel® HD Graphics S500 Intel® HD Graphics S500, AMD Radeon® R7 M260 Graphics leatures DirectX® 11.3 upport DirectX® 11.1 Graphics leatures DirectX® 11.1 Stared memory depending on main memory size		LIFEBOOK A555	LIFEBOOK A555/G	
Graphics features DirectX** 11 support DirectX** 11 support Graphics notes Shared memory depending on main memory size Obtained video memory 2 CB (DDR3 VRAM) Shared video memory up to 1,095 MB DC-in 1 DS 2.0 total 3 (1 x.Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 MBM VGA 1 MBM 1 VGA 1 MBM 1 WGA 1 MBM 1 WGA 1 WGA 1 WGA 1 WGA 1 WGA 1 WGA SDJSDHOS/DXC WGA WLAN tots Spill-resistant isolated keyboard with number block	Max. resolution external display	1,920 x 1,200 pixel	1,920 x 1,200 pixel	
Graphics notes Shared memory depending on main memory size Decidicated video memory 2 GB (DDR3 VRAM) Bared video memory up 1.695 MB Dimeratics DC-in 1 USB 2.0 total 3 (1 x.Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HDMI 1 Ethemet (R-45) 1 Memory card slots SD/SDMC/SDXC Keyboard and pointing devices Spill-resistant isolated keyboard with number block Touchpad Status LED WINeless technologies Spill-resistant isolated keyboard go country-specific regulations. WIN encryption WEP, WPA, WPA2 WUAN notes Import and usage according to country-specific regulations. WID support Yes (with Intel W-LAN) Power supply Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 5tandard Adapter, 0.320 kg, 126x50x30 mm Rated frequency range 50 Hz - 00 Hz Rated frequency range 50 Hz - 00 Hz Is battery U Ion battery 6 cell, 4500 mAh, 48 Wh Runtine 1st battery </td <td>Graphics brand name</td> <td>Intel[®] HD Graphics 5500</td> <td>Intel® HD Graphics 5500, AMD Radeon™ R7 M260</td>	Graphics brand name	Intel [®] HD Graphics 5500	Intel® HD Graphics 5500, AMD Radeon™ R7 M260	
Dedicated video memory 2 GB (DDR3 VRAM) Shared video memory up to 1,695 MB Interfaces DC-in 1 USB 2.0 total 3 (1 x Anytime USB Charge Functionality - depending on BIOS setting) VGA MDM 1 HDM1 1 HDM1 1 Memory card slots SDSDHC/SDXC Keyboard and pointing devices Spil-resistant isolated keyboard with number block Touchpad Status LED WILAN encryption WFP, WPA, WPA2 WILAN encryption WFP, WPA, WPA2 WILAN encryption WFP, WPA, WPA2 WILAN encryption VFP, WPA, WPA2 WILAN encryption Ves (with intel W-LAN) Power s	Graphics features	DirectX [®] 11 support	DirectX [®] 11.1	
Shared video memory up to 1,695 MB Interfaces DC in 1 USB 2.0 total 1 USB 3.0 total 3 (1 x Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HDMI 1 Ethernet (R)-45) 1 Keyboard and pointing devices Spill-resistant isolated keyboard with number block Touchpad Status LED Wilekes technologies Spill-resistant isolated keyboard with number block Touchpad Status LED Wilekest technologies Spill-resistant isolated keyboard with number block Touchpad Status LED Wilekest technologies Spill-resistant isolated keyboard with number block Touchpad Status LED Wilekest technologies Spill-resistant isolated keyboard with number block Touchpad Status LED Wilekest technologies Spill-resistant isolated keyboard with number block Touchpad Status LED Wilekest technologies Import and usage according to country-specific regulations. Bitetooth v4.0 Wilek encryption WEP, WPA, WPA2 Work encryption WEP, WPA, WPA2 Bitetooth v4.0 Wilek encryption WEP, WPA, UPA (UR, NA) Power supply T A Cadapter 19 V 90 W (4, 74, A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated frequency range Statet frequency range	Graphics notes	Shared memory depending on main memory size		
Interfaces DC-in 1 USB 2.0 total 1 USB 2.0 total 1 USB 2.0 total 3 (1 × Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HOMI 1 Ethernet (RJ-45) 1 Memory card slots SD/SDH/C/SDXC Keyboard and pointing devices Spill-resistant isolated keyboard with number block Touchpad Status LED Wireless technologies Bluetooth V4.0 WLAN notes Import and usage according to country-specific regulations. WiDi support Yes (with Intel W-LAN) Power supply AC Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 50 Hz - 60 Hz Ist battery U-I lon battery 6- 61 Hz Ist battery U-I lon battery 6- 61 Hz Ist battery U-I lon battery 6- 61 Hz Ist battery U-I lon battery fer may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Please refer to the Eco Please refer to the Eco	Dedicated video memory		2 GB (DDR3 VRAM)	
DC in 1 USB 2.0 total 1 USB 2.0 total 3 (1 × Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HDMI 3 (I × Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HDMI 1 LThernet (RJ-45) 1 USB 3.0 total S DISDHO'SDXC Keyboard and pointing devices Spill resistant isolated keyboard with number block Touchpad Status LED Wireless technologies Bluetooth v4.0 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WiDi support Yes (with Intel W-LAN) Power supply AC Adapter 19 V / 90 W (A.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 50 Hz - 60 Hz Status LED Battery notes Battery Licen battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to Bh (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery Licen battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to Bh (MobilMark2012, office productivity mode) configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight 0.2.4 kg (5.3 lb) Weight notes Weight the may wary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance	Shared video memory	up to 1,695 MB		
DC in 1 USB 2.0 total 1 USB 2.0 total 3 (1 × Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HDMI 3 (I × Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HDMI 1 LThernet (RJ-45) 1 USB 3.0 total S DISDHO'SDXC Keyboard and pointing devices Spill resistant isolated keyboard with number block Touchpad Status LED Wireless technologies Bluetooth v4.0 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WiDi support Yes (with Intel W-LAN) Power supply AC Adapter 19 V / 90 W (A.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 50 Hz - 60 Hz Status LED Battery notes Battery Licen battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to Bh (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery Licen battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to Bh (MobilMark2012, office productivity mode) configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight 0.2.4 kg (5.3 lb) Weight notes Weight the may wary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance	Interfaces			
VSB 3.0 total 3 (1 x Anytime USB Charge Functionality - depending on BIOS setting) VGA 1 HDMI 1 Ethernet (R)-45) 1 Memory card slots SD/SDHC/SDXC Keyboard and pointing devices Spill-resistant isolated keyboard with number block Touchpad Status LED Wirkless technologies Bluetooth v4.0 WLAN notes Import and usage according to country-specific regulations. WiDI support Yes (with Intel W LAN) Power supply AC Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated frequency range 50 Hz - 60 Hz Sta battery U-10 hattery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to 8h (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery tife may vary depending on product model, configuration, applications, power management settings and frequency results utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions // Weight / Environmental 378 mm (14.88 inch	DC-in	1		
VGA 1 HDMI 1 HDM	USB 2.0 total	1		
HDMI 1 Ethernet (RJ-45) 1 Memory card slots SD/SDHC/SDXC Keyboard and pointing devices SD/SDHC/SDXC Keyboard and pointing devices Suppliersistant isolated keyboard with number block Touchpad Status LED Wireless technologies Bluetooth WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WIDI support Yes (with Intel W-LAN) Power supply AC Adapter AC Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 100 V - 240 V (AC Input) Rated toxitage range 100 V - 240 V (AC Input) Rated toxitage range 100 V - 240 V (AC Input) Rated toxitage range 100 V - 240 V (AC Input) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)	USB 3.0 total	3 (1 x Anytime USB Charge Functionality - depending on BIOS setting)		
Ethernet (R)-45) 1 Memory card slots SD/SDHC/SDXC Keyboard and pointing devices Spill-resistant isolated keyboard with number block Touchpad Touchpad Status LED Wireless technologies Wireless technologies WEP, WPA, WPA2 WLAN encryption WEP, WPA, WPA2 WLN notes Import and usage according to country-specific regulations. WiDi support Yes (with Intel W-LAN) Power supply Ac Adapter Ac Adapter 19 V / 90 W (4, 74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 50 Hz - 60 Hz Ist battery Li-Ion battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to 8h (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery Life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery irecharge time depends on usage. Noise emission Please refer to the Eco Declaration Dimensions (Weight / Environmental Touchies depending on actual configuration. <	VGA			
Memory card slots SD/SDHC/SDXC Keyboard and pointing devices Spill-resistant isolated keyboard with number block Touchpad status LED Wireless technologies Touchpad Wireless technologies V4.0 Witeless technologies Wireless technologies Wireless technologies V9.0 Wireless technologies Wireless technologies Wireless technologies Import and usage according to country-specific regulations. Wireless technologies Import and usage according to country-specific regulations. Work support Yes (with Intel W-LAN) Power supply Xex (Adapter 0 Ac Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated frequency range 50 Hz - 60 Hz Status LED Status LED Rated frequency range 50 Hz - 60 Hz Status LED Status LED Runtime 1st battery Li-lon battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery Up 08 (Mobil/Mark2012, office productivity mode) up to 6.5 h (Mobil/Mark2012, office productivity mode) Battery Itile may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.	HDMI	1		
Keyboard and pointing devices Spill-resistant isolated keyboard with number block Touchpad Status LED Wireless technologies Wireless technologies Bluetooth v4.0 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WIDI support Yes (with Intel W-LAN) Power supply Yes (with Intel W-LAN) Rated frequency range 10 V / 240 V (AC Input) Rated voltage range 100 V - 240 V (AC Input) Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 50 Hz - 60 Hz Sta battery Li-Ion battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to 8h (Mobil/Mark2012, office productivity mode) up to 6.5 h (Mobil/Mark2012, office productivity mode) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Dimensions (Weight / Environmental 778 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight notes Weight may vary depending on actual configuration Weight notes	Ethernet (RJ-45)	1		
Spill-resistant isolated keyboard with number block Touchpad Status LED Wireless technologies Bluetooth v4.0 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WID support Yes (with Intel W-LAN) Power supply Yes (with Intel W-LAN) Power supply VAC (Input) Rated voltage range 100 V - 240 V (AC Input) Rated voltage range 50 Hz - 60 Hz Sta battery Li-lon battery fo-cell, 4500 mAh, 48 Wh Runtime Ist battery up to 8h (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Dimensions (W × D × H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight notes Weight may vary depending on actual configuration Dimensions (W × D × H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight notes Weight may vary depending on actual configuration	Memory card slots	SD/SDHC/SDXC		
Spill-resistant isolated keyboard with number block Touchpad Status LED Wireless technologies Bluetooth v4.0 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WID support Yes (with Intel W-LAN) Power supply AC Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated voltage range 50 Hz - 60 Hz Sta battery Li-10n battery fo-cell, 4500 mAh, 48 Wh Runtime 1st battery Li-10n battery fo-cell, 4500 mAh, 48 Wh Runtime 1st battery Up to 8h (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental To the Eco Declaration Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight notes Weight may vary depending on actual configuration	Kevboard and pointing devices			
Bluetooth v4.0 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WiD support Yes (with Intel W-LAN) Power supply AC Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 50 Hz - 60 Hz Ist battery Li-Ion battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery Up to 8h (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance		Touchpad		
WLAN encryptionWEP, WPA, WPA2WLAN notesImport and usage according to country-specific regulations.WiD supportYes (with Intel W-LAN)Power supplyAC Adapter19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mmRated voltage range100 V - 240 V (AC Input)Rated frequency range50 Hz - 60 HzIst batteryLi-lon battery 6-cell, 4500 mAh, 48 WhRuntime 1st batteryup to 8h (MobilMark2012, office productivity mode)up to 8.1 (MobilMark2012, office productivity mode)Up to 8.1 (MobilMark2012, office productivity mode)Up to 8.5 h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationNeight / EnvironmentalDimensions (W x D x H)378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight notesWeight notesWeight may vary depending on actual configurationOperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance	Wireless technologies			
WLAN noteImport and usage according to country-specific regulations.WiDi supportYes (with Intel W-LAN)Power supply19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mmRated voltage range100 V - 240 V (AC Input)Rated voltage range50 Hz - 60 Hz1st batteryLi-Ion battery 6-cell, 4500 mAh, 48 WhRuntime 1st batteryup to 8h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationDimensions / Weight / Environmental978 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight notesWeight may vary depending on actual configurationOperating ambient temperature5 - 35 °C (41 - 95 °F)ComplianceCompliance		v4.0		
WiDi support Yes (with Intel W-LAN) Power supply AC Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated voltage range 50 Hz - 60 Hz Rated frequency range 50 Hz - 60 Hz Up to 8h (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight may vary depending on actual configuration Weight notes Weight may vary depending on actual configuration Gompliance	WLAN encryption	WEP, WPA, WPA2		
Power supply AC Adapter 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mm Rated voltage range 100 V - 240 V (AC Input) Rated frequency range 50 Hz - 60 Hz Ist battery Li-Ion battery 6-cell, 4500 mAh, 48 Wh Runtime 1st battery up to 8h (MobilMark2012, office productivity mode) up to 6.5 h (MobilMark2012, office productivity mode) Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. Noise emission Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight 0.4 kg (5.3 lb) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance	WLAN notes	Import and usage according to country-specific regulation	DNS.	
AC Adapter19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mmRated voltage range100 V - 240 V (AC Input)Rated frequency range50 Hz - 60 HzIst batteryLi-lon battery 6-cell, 4500 mAh, 48 WhRuntime 1st batteryup to 8h (MobilMark2012, office productivity mode)up to 6.5 h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / Environmental378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)378 mm (14.89 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight notesWeight may vary depending on actual configurationGoperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance	WiDi support	Yes (with Intel W-LAN)		
AC Adapter19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Standard Adapter, 0.320 kg, 126x50x30 mmRated voltage range100 V - 240 V (AC Input)Rated frequency range50 Hz - 60 HzIst batteryLi-Ion battery 6-cell, 4500 mAh, 48 WhRuntime 1st batteryup to 8h (MobilMark2012, office productivity mode)up to 6.5 h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / Environmental378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)378 mm (14.89 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight notesWeight may vary depending on actual configurationGoperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance	Power supply			
Rated voltage range100 V - 240 V (AC Input)Rated frequency range50 Hz - 60 HzIst batteryLi-lon battery 6-cell, 4500 mAh, 48 WhRuntime 1st batteryup to 8h (MobilMark2012, office productivity mode)up to 6.5 h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / Environmental378 mm (14.88 inch) × 256 mm (10.08 inch) × 30.9 mm (1.22 inch)Weight notesWeight may vary depending on actual configurationOperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance	11 /	19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, Stand	lard Adapter, 0.320 kg, 126x50x30 mm	
Rated frequency range50 Hz - 60 Hz1st batteryLi-Ion battery 6-cell, 4500 mAh, 48 WhRuntime 1st batteryup to 8h (MobilMark2012, office productivity mode)up to 6.5 h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / Environmental378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight notesWeight may vary depending on actual configurationOperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance	-			
Tst batteryLi-lon battery 6-cell, 4500 mAh, 48 WhRuntime 1st batteryup to 8h (MobilMark2012, office productivity mode)up to 6.5 h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / Environmental378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight notesWeight may vary depending on actual configurationSecond formationOperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance				
Runtime 1st batteryup to 8h (MobilMark2012, office productivity mode)up to 6.5 h (MobilMark2012, office productivity mode)Battery notesBattery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / Environmental378 mm (14.88 inch) × 256 mm (10.08 inch) × 30.9 mm (1.22 inch)378 mm (14.88 inch) × 256 mm (10.08 inch) × 30.9 mm (1.22 inch)Weight notesWeight may vary depending on actual configuration5 - 35 °C (41 - 95 °F)ComplianceComplianceCompliance	· · · ·			
features utilized. Battery recharge time depends on usage.Noise emissionNoise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / EnvironmentalDimensions (W x D x H)378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight2.4 kg (5.3 lb)Weight notesWeight may vary depending on actual configurationOperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance	Runtime 1st battery			
Noise emissionPlease refer to the Eco DeclarationPlease refer to the Eco DeclarationDimensions / Weight / EnvironmentalDimensions (W x D x H)378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch)Weight2.4 kg (5.3 lb)Weight notesWeight may vary depending on actual configurationOperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance	Battery notes	Battery life may vary depending on product model, configuration, applications, power management settings and		
Dimensions / Weight / Environmental Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight 2.4 kg (5.3 lb) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance Vertice	Noise emission			
Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight 2.4 kg (5.3 lb) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance Compliance	Noise emission	Please refer to the Eco Declaration	Please refer to the Eco Declaration	
Dimensions (W x D x H) 378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mm (1.22 inch) Weight 2.4 kg (5.3 lb) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance Compliance	Dimensions / Weight / Environmental			
Weight 2.4 kg (5.3 lb) Weight notes Weight may vary depending on actual configuration Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance Complement of the second sec	· · · · · · · · · · · · · · · · · · ·	378 mm (14.88 inch) x 256 mm (10.08 inch) x 30.9 mr	n (1.22 inch)	
Weight notesWeight may vary depending on actual configurationOperating ambient temperature5 - 35 °C (41 - 95 °F)Compliance				
Operating ambient temperature 5 - 35 °C (41 - 95 °F) Compliance				
Compliance				
	· · ·	· · · ·		
	Compliance Model	Fujitsu LIFEBOOK A555		

Compliance			
Europe	CE WEEE		
Global	RoHS (Restriction of hazardous substances) ENERGY STAR® 6.0 Microsoft Operating Systems (HCT / HCL entry / WHQL)		
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates		
Additional Software			
Additional software (included as a CD/ DVD)	Drivers & Utilities DVD (DUDVD)		
Security			
Physical Security	Kensington Lock support	Kensington Lock support	
System and BIOS Security	Computrace [®] ready BIOS Optional: Trusted platform module (TPM 1.2)	Computrace® ready BIOS Optional: Trusted platform module (TPM 1.2)	
User Security	User and supervisor BIOS password Hard disk password	User and supervisor BIOS password Hard disk password	

Warranty	
Warranty period	1 year
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfe	ct extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	3 years after end of product life
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Recommended Accessories

Casual Backpack 16	The Casual Backpack 16 is designed to fit an up to 15.6-inch widescreen notebook. It provides additional storage area, extra-large compartments and zip able pockets to store everything you need for work, school or travel including. This also includes an expandable file storage as well as a large separate zip-compartment to store books, accessories, and more. A small front pocket and two side mesh pockets complete the backpack. Shoulder straps and a top handle are padded for pleasant carrying comfort.	Order Code: S26391-F1192-L167
Wireless Mouse WI200	The Wireless Mouse WI200 uses the latest wireless 2.4 GHz technology, and a high-resolution 1000 dpi optical sensor to give you the precision and reliability you need. Sporting a compact design with a stylish black finish, the WI200 wireless mouse is well suited to all environments and to each user whether right or left handed.	Order Code: S26381-K462-L100
SOUNDSYSTEM DS E2000 Air	The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600

UC&C USB Value Headset



The FUJITSU UC&C USB Value Headset is a lightweight bi-aural full-size stereo headset with high wearing comfort. This Lync-tested USB-Headset has an appropriate Inline-Controller which supports easy call management. A noise cancelling microphone facilitates undisturbing clear phone calls.

Order Code: S26391-F7139-L20

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU LIFEBOOK A555 and LIFEBOOK A555G, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU LIFEBOOK A555 and LIFEBOOK A555G, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions Website: www.fujitsu.com/fts 2015-03-24 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their

own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions