

Data Sheet

FUJITSU Server PRIMERGY RX2530 M5 Rack Server

Maximum productivity in a 1U housing

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers as well as hyper-converged multi-node servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

FUJITSU Server PRIMERGY RX rack systems are versatile rack-optimized servers providing best-in-class performance and energy efficiency, and thus form the "standard" in each data center. PRIMERGY RX servers deliver more than 20 years of development and production know-how resulting in extremely low failure rates below market average, and lead to continuous operations and outstanding hardware availability.

PRIMERGY RX2530 M5

The FUJITSU Server PRIMERGY RX2530 M5 is a rack server that provides high performance, expandability and energy efficiency in a 1U space-saving housing. The PRIMERGY RX2530 M5 is ideal for virtualization, scale-out scenarios, and small databases as well as for high performance computing thanks to the high performance of the new Intel® Xeon® Processor Scalable Family CPUs with up to 28 cores and the latest DDR4 memory technology. Moreover, the RX2530 M5 delivers a great expandability by supporting up to 3,072 GB of main memory and the capability to use up to 12x Intel® Optane™ DC Persistent

Memory NV-DIMM modules. It is future-proof with M.2 device support and the latest iRMC S5 for server management of the next generation. Up to 10 hard disk drives or optionally high-speed PCIe SSDs offer a flexible storage configuration option. A variety of onboard DynamicLoM options, plus its dual-port embedded LAN meet future requirements, cost-optimized. The limited space of a 1U chassis offers highly efficient power supply units and their redundancy on demand. The optional Cool-safe® Advanced Thermal Design this will result in lower operational costs.



Features & Benefits

Main Features	Benefits
<p>Innovation meets Performance</p> <ul style="list-style-type: none"> Wide choice of different types of Intel® Xeon® Scalable Processor Family. Each processor offers up to 28 cores, up to 56 threads, 12 memory channels enabling a significantly higher performance and efficiency. They rely on Intel® UltraPath Interconnect for an increased data rate between the CPUs. Intel® Optane™ DC persistent memory is an innovative memory technology that delivers a unique combination of affordable large capacity and persistence (non-volatility). It revolutionizes the data center memory-storage hierarchy of the past and brings massive data sets closer to the CPU for faster time to insight. In total, up to 7,680 GB main memory in a mixed mode (non-volatile memory + DDR4 @ 2,933 MT/s) are available. <p>Enhanced Features for enhanced Computing</p> <ul style="list-style-type: none"> The RX2530 M5 comes with onboard LAN for basic LAN, DynamicLoM via OCP slot for extended requirements. A mix&match storage drive bay configuration offers the choice of either up to 8x 2.5-inch HDD/SSD + 1x ODD or up to 10x 2.5-inch, thereof optionally max. 10x PCIe 2.5-inch SSD SFF, complemented by internal M.2 devices for hypervisor installations. Our power supply units with up to 96% energy efficiency and Fujitsu's Cool-safe® Advanced Thermal Design for higher ambient temperatures in the data center are available for this server. <p>Foundation for Trust and Security</p> <ul style="list-style-type: none"> Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control, free-of-charge BIOS, firmware and selected software updates plus TPM2.0 modules and latest operating system support are a great addition. <p>Revolutionize data center management</p> <ul style="list-style-type: none"> Fujitsu ServerView Suite is a free-of-charge management software including tools for installation and deployment, permanent status monitoring and control as well as BIOS, firmware and selected software updates. In addition FUJITSU Software Infrastructure Manager (ISM) provides converged management across multiple data centers. The new ISM Essential license, available free-of-charge provides essential server management and converged monitoring functions. 	<ul style="list-style-type: none"> Ready for the future and data growth scenarios with the performance of two processors – marking the standard of tomorrow with an increase in computing power. Several innovations make this new CPU generation (code-named “Cascade Lake”) even more powerful than the current-generation Intel® Xeon® Scalable processors, enabling robust compute capability and increased memory bandwidth for demanding workloads. Intel® Optane™ DC persistent memory technology will transform critical data workloads – from cloud and databases, to in-memory analytics, and content delivery networks. The right Ethernet connection for all: Basic via onboard LAN, extended with DynamicLoM via OCP guarantees the highest flexibility to integrate the server into existing infrastructures – now and in future without overhauling the existing infrastructure. Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa. On top of that, this server is not only “greener”, but also less expensive over time. Cool-safe® ATD and highly efficient hot-plug power supplies save energy costs. These features ensure lifecycle investment protection while the comprehensive tools of the Fujitsu ServerView Suite ease the administrators’ life. Moreover, hardware and software security features are very important in a fast-paced world, especially considering cybercrime. Fujitsu offers comprehensive infrastructure management and server management solutions which is key to efficient data center operations. They provides all the functions for flexible and automated 24x7 IT operations and improves end-user productivity via intelligent and innovative system management solutions. ISM helps improve data center efficiency and overall IT Productivity with converged infrastructure management, paving the path to software-defined data center.

Technical details

PRIMERGY RX2530 M5

Base unit	PRIMERGY RX2530 M5 LFF	PRIMERGY RX2530 M5 SFF	PRIMERGY RX2530 M5 SFF	PRIMERGY RX2530 M5 SFF	PRIMERGY RX2530 M5 SFF
Housing types	Rack	Rack	Rack	Rack	Rack
Storage drive architecture	4x 3.5-inch SAS/SATA	4x 2.5-inch SAS/SATA	8x 2.5-inch SAS/SATA	10x 2.5-inch SAS/SATA/PCIe	10x 2.5-inch SATA/NVMe
Power supply	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug
Product Type	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server

Mainboard

Mainboard type	D3383-B	D3383-B	D3383-B	D3483-B	D3483-B
Chipset	Intel® C624				
Processor quantity and type	1 - 2 x Intel® Xeon® Processor Scalable Family				

Intel® Xeon® Bronze Processor Intel® Xeon® Bronze 3204 (6C, 1.90 GHz, TLC: 8.25 MB, Turbo: 1.90 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.50 GHz, AVX Turbo 1.50 GHz)

Intel® Xeon® Silver Processor Intel® Xeon® Silver 4208 (8C, 2.10 GHz, TLC: 11 MB, Turbo: 2.50 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.60 GHz, AVX Turbo 2.00 GHz)

Intel® Xeon® Silver 4210 (10C, 2.20 GHz, TLC: 13.75 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.90 GHz, AVX Turbo 2.30 GHz)

Intel® Xeon® Silver 4214 (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)

Intel® Xeon® Silver 4214Y (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)

Intel® Xeon® Silver 4215 (8C, 2.50 GHz, TLC: 11 MB, Turbo: 3.00 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)

Intel® Xeon® Silver 4216 (16C, 2.10 GHz, TLC: 22 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 100 W, AVX Base 1.40 GHz, AVX Turbo 2.30 GHz)

Intel® Xeon® Gold Processor

Intel® Xeon® Gold 5215 (10C, 2.50 GHz, TLC: 13.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 5215L (10C, 2.50 GHz, TLC: 13.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 5215M (10C, 2.50 GHz, TLC: 13.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 5217 (8C, 3.00 GHz, TLC: 11 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 115 W, AVX Base 2.50 GHz, AVX Turbo 3.00 GHz)
Intel® Xeon® Gold 5218 (16C, 2.30 GHz, TLC: 22 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Gold 5218B (16C, 2.30 GHz, TLC: 22 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Gold 5220 (18C, 2.20 GHz, TLC: 24.75 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)
Intel® Xeon® Gold 5220S (18C, 2.70 GHz, TLC: 24.75 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.20 GHz)
Intel® Xeon® Gold 5222 (4C, 3.80 GHz, TLC: 16.5 MB, Turbo: 3.90 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 105 W, AVX Base 3.80 GHz, AVX Turbo 3.80 GHz)
Intel® Xeon® Gold 6209U (20C, 2.10 GHz, TLC: 27.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6210U (20C, 2.50 GHz, TLC: 27.5 MB, Turbo: 3.20 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 1.90 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6212U (24C, 2.40 GHz, TLC: 33 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 6222V (20C, 1.80 GHz, TLC: 27.5 MB, Turbo: 2.40 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 115 W, AVX Base 1.60 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6226 (12C, 2.70 GHz, TLC: 19.25 MB, Turbo: 3.50 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 125 W, AVX Base 2.30 GHz, AVX Turbo 3.10 GHz)
Intel® Xeon® Gold 6230 (20C, 2.10 GHz, TLC: 27.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6230T (20C, 2.10 GHz, TLC: 27.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6234 (8C, 3.30 GHz, TLC: 24.75 MB, Turbo: 4.00 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 130 W, AVX Base 2.8 GHz, AVX Turbo 3.70 GHz)
Intel® Xeon® Gold 6238 (22C, 2.10 GHz, TLC: 30.25 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 140 W, AVX Base 1.70 GHz, AVX Turbo 2.50 GHz)
Intel® Xeon® Gold 6238L (22C, 2.10 GHz, TLC: 30.25 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 140 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz)
Intel® Xeon® Gold 6238M (22C, 2.10 GHz, TLC: 30.25 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 140 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz)
Intel® Xeon® Gold 6240 (18C, 2.60 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.00 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6240L (18C, 2.60 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.00 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6240M (18C, 2.60 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.00 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6240Y (18C, 2.60 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.00 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6242 (16C, 2.80 GHz, TLC: 22 MB, Turbo: 3.50 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 2.30 GHz, AVX Turbo 3.10 GHz)
Intel® Xeon® Gold 6244 (8C, 3.60 GHz, TLC: 24.75 MB, Turbo: 4.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 3.00 GHz, AVX Turbo 3.90 GHz)
Intel® Xeon® Gold 6246 (12C, 3.30 GHz, TLC: 24.75 MB, Turbo: 4.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 2.90 GHz, AVX Turbo 3.80 GHz)
Intel® Xeon® Gold 6248 (20C, 2.50 GHz, TLC: 27.5 MB, Turbo: 3.20 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 1.90 GHz, AVX Turbo 2.80 GHz)
Intel® Xeon® Gold 6252 (24C, 2.10 GHz, TLC: 35.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 150 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)

Intel® Xeon® Gold 6254 (18C, 3.10 GHz, TLC: 24.75 MB, Turbo: 3.90 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 200 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz) <http://www.fujitsu.com/global/products/computing/servers/primergy/rack/rx2530m5/>

Intel® Xeon® Gold 6262V (24C, 1.90 GHz, TLC: 33 MB, Turbo: 2.50 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 135 W, AVX Base 1.60 GHz, AVX Turbo 2.80 GHz)

Components

Optical drives

Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I
 DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I

Hard disk drives

HDD SATA, 6 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
 HDD SATA, 6 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
 HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
 HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
 HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
 HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
 HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
 HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
 HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
 HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical

Hard disk drives

HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical

Solid-State-Drive

SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.5 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD M.2 SATA, 6 Gb/s, 480 GB, non hot plug, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise

Solid-State-Drive

SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 2.3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 2.3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)

PCIe SSD & SATA DOM SSD

PCIe-SSD SFF, 750 GB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 30 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.2 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 4 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 4 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 0.6 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.1 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 2 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 2 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 0.6 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD AIC, 750 GB, Write-Intensive, HHHL, Flash drive, 30 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD AIC, 375 GB, Write-Intensive, HHHL, Flash drive, 30 DWPD (Drive Writes Per Day for 5 years)
Dual microSD 64GB Enterprise

SCSI / SAS Controller

LSI PSAS CP400e LP SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8
Fujitsu PSAS CP403i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
Fujitsu PSAS CP400i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
Fujitsu PSAS CP400e FH SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8

RAID Controller	Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP540e LP, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
Communication, Network	Converged Network Adapter 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Cavium)
	Ethernet Ctrl. 1 x 100 Gbit/s PCIe 3.0 x16 QSFP28 (Cavium)
	Ethernet Ctrl. 1 x 100 Gbit/s PCIe 3.0 x16 QSFP28 (Mellanox)
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Cavium)
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 SFP+ (Cavium)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Cavium)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Mellanox)
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®)
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®)
	Ethernet Ctrl. 2 x 40 Gbit/s PCIe 3.0 x16 QSFP (Mellanox)
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Cavium)
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Intel®)
	Ethernet Ctrl. 4 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®)
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®)
	InfiniBand HCA 1 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed (Mellanox)
	InfiniBand HCA 2 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed (Mellanox)
	Interface modul for Dynamic LoM 2 x 10 Gbit/s RJ45 (Intel®)
	Interface modul for Dynamic LoM 2 x 10 Gbit/s SFP+ (Intel®)
Interface modul for Dynamic LoM 4 x 10 Gbit/s SFP+ (Intel®)	
Interface modul for Dynamic LoM 4 x 1 Gbit/s RJ45 (Intel®)	
MPO x 40 Gbit/s ()	
Omni Path 1 x PCIe 3.0 x16 (Intel®)	
Graphics	NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3 x miniDP

Rack infrastructure	Rackmount kit full extraction (815mm), tool less mounting, length variable 559-914mm Rackmount kit full extraction (815mm), tool less mounting, length variable 559-914mm Rackmount kit tool less mounting Cable Management 1U for PRIMECENTER- and 3rd-party racks
Warranty	
Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Product Support Services - the perfect extension	
Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years after end of product life
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Server PRIMERGY RX2530 M5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PRIMERGY RX2530 M5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2019-06-01 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED