# **DATA SHEET**



# 15ft DisplayPort™ Male to VGA Male Active Adapter Cable - Black (TAA Compliant)

Connect the DisplayPort output of a computer to the VGA input of a computer monitor

#### **OVERVIEW**

This adapter cable is an ideal solution for connecting the DisplayPort output of a laptop to a computer monitor which accepts a VGA input. This cable carries an analog video signal, supports up to a 1920x1200 resolution and meets the requirements of high performance applications.

#### **FEATURES**

- Directly connect a DisplayPort output to a VGA input
- Carries an analog video signal
- Supports up to a 1920x1200 resolution

## ITEM DESCRIPTION

C2G54343 15ft DisplayPort Male to VGA Male Active Adapter Cable - Black (TAA Compliant)



# **DATA SHEET**

# **SPECIFICATIONS:**

DisplayPort Male to VGA Male Active Adapter Cable -Black (TAA Compliant)

## **ELECTRICAL SPECIFICATIONS:**

- Voltage Rating: 30v

Conductor Resistance: @ 20°C max
Insulation Resistance: 10MΩ/km

- Time Delay: 5.2ns/m (max)

- Attenuation:

5.02dB@100-450MHz 7.69dB@1GHz 12.595dB@2GHz 17.495dB@3GHz 22.395dB@4GHz 27.295dB@5GHz 32.195dB@6GHz 37.095dB@7GHz

#### PHYSICAL SPECIFICATIONS:

Operating Temperature: 0°C to 50°CStorage Temperature: -25°C to 70°C

Approvals: CEWarranty: Lifetime

## PHYSICAL CHARACTERISTICS:

#### Conductor (2 Conductors, 5 Pair):

- Conductor: 30AWG (7/0.1TC)
- Insulation: FM-PE, ID:0.8±0.05mm
- Color: White/Brown, White/Red, White/Orange, White/Green, White/Blue
- Drain: 30AWG (7/0.1TC) HD-PE ID:0.56±0.05
- Shield: AL-Mylar Wrap Coverage—100%

#### **Conductor (5 Conductors):**

- Conductor: 30AWG (7/0.1TC)
- Insulation: HD-PE, ID:0.56±0.05mm
- Color: Red/Orange/Yellow/Green/ White

#### **Overall Cable**

- Jacket: PVC
- Shield: AL-Mylar—Coverage 100% Braid—16/9/0.12
- Drain: 2:30AWG (7/0.08 BC)
- OD: 6.5±0.2

C2G

A brand of | egrand